

Stand Alone Oxygen Deficiency Monitor

Gas Detection For Life

OX-600



RKI's Model OX-600 is an indoor, standalone monitor that detects Oxygen (O2) with a range of 0-25.0 % volume with 0.1% increments. It's sleek, low-profile design is equipped with a unique tri-color display, which changes color as oxygen levels reach each alarm level. The OX-600 has 2 preset alarms, and comes ready to operate with a simple wall mount bracket and 10 foot power cord. It is capable of operating with three different power options; 115 VAC, 24 VDC or alkaline batteries. If Oxygen is present, the user is notified by an audible alarm tone and the multicolored LED digital display.

The OX-600 uses a fast responding low-cost plug-in style galvanic cell sensor. This long life sensor is fieldreplaceable with no special tools required. The sensor can also be remotely mounted with an optional remote sensor cable.

RKI Instruments, Inc. • 33248 Central Ave. Union City, CA 94587 • Phone (800) 754-5165 • (510) 441-5656 • Fax (510) 441-5650



Model OX-600 Specifications	
Detection Principle	Galvanic cell
Gas Detected	Oxygen (O2)
Detection Range	0 ~ 25 vol%
Display Resolution	0.1 vol%
Sampling Method	Diffusion or remote sampling method with optional sensor extender cable
Indication Accuracy*	Within ±0.7 vol%
Response Time*	90% Response within 30 seconds (T90)
Alarm Levels	Two preset alarms (L-LL), alarm 1 = 19.5% vol, alarm 2 = 18.0% vol (other settings available)
Display of Alarm	1st gas alarm: gas concentration reading blinks or orange light, flashing AL1 light or orange light, buzzer 2nd gas alarm: gas concentration reading blinks or red light, flashing AL2 light or red light, buzzer
Alarm Logic	Latching or Non-latching (including trouble alarm)
Alarm Contact	Dry contact, normally-open or normally closed (default setting is normally open)
Display	Digital LCD (3 digits, 7 segments / Green, Orange, Red) (For Alkaline battery version, the back light will be OFF during normal operation)
Trouble Alarm / Self-Diagnosis	System trouble / sensor connection trouble
Display of Trouble Alarm	Buzzer / flashing of red error message
Relay Contact Rating	125VAC, 1A or 30VDC, 1A (Resistive load)
Output Signal	$4\sim 20mA$ (Non-isolated, Resistive load under $300\Omega)$ or 0 - 1VDC (Non-isolated) *only for 0 - 1VDC Alkaline battery specification
Extender Cable	Extender cable with remote box (3 m, 5 m, 10 m, & 20 m lengths available)
Power Sources	(120VAC±10%, 50/60Hz,) 24VDC±10%, or AA alkaline battery (2 each)
Power Consumption	AC specification: MAX 3.5VA, DC specification: MAX 2W
Continuous Operation (for Alkaline Battery version)	1 year (no alarm, no indication)
Operating Temperature	0 ~ 104°F (-17 ~ 40°C)
Operating Humidity	0 - 90%RH (non-condensing)
Mounting Equipment	Wall mounting type (by using accessory mounting plate or mount at one switch box) Cable inlet: Up, down and left/right, or rear side
Dimension	Body: approx. 3.15"(W) x 4.72"(H) x 1.2"(D) (80(W) x 120(H) x 35.5(D)mm)
Weight	AC specification: approx. 7.05 oz (200g), DC specification: approx. 6.34 oz (180g), Alkaline battery specification: approx. 8.11 oz (230g)

*Under normal conditions





Authorized Distributor: