| | | | Τ | |
|---|--|---|------------------------|-------------|
| | | ary Release | 11/7/07 | |
| | P2 PDC 080 |)425-01 | 04/28/08 | |
| | DO O O O O O O O O O O O O O O O O O O | Beacon 200 Detector/Tra Terminal Stri Cable | | |
| White Green | | | | |
| Oxygen Detector | | | | |
| Notes: 1. This drawing may oxygen transmitte | be also used with 0-1 r 65-2321RK-100. | 00% | | |
| DO NOT SCALE DRAWING Deburr Break Edges .010 R | All Dimensions In Inches Unless Otherwise Noted. | DVI | RKI Instruments | Inc. |
| Tolerances & Finishes Unless | MATERIAL: N/A | INSTRUMENTS | www.rkiinstruments.com | |
| Otherwise Noted: .XX ± .010 Angles ± 0° 30' | rwise Noted: Angles ± 0° 30' TITLE: Wiring Diagram, 65-2321RK to Beacon 200 | | | |
| .XXX ± .005 Conc010 TIR | FINISH: N/A | | | |
| Fractions ± .015 Finish 125 | | ∆ DRAWN | PART NUMBER: | REVISION: |
| Finish for O-ring Grooves, 3 Sides 32/ | COALE, Naza | BY: DJ | 65-2321RK-R05 | P2 |
| <u> </u> | SCALE: None | APPROVED BY: | DATE: 11/7/07 | PAGE 1 OF 1 |